

Plywood

Trade Essentials[®]



Laminex[™]
NEW ZEALAND

Plywood

B/B & B/D Radiata Pine Plywood

Trade Essentials® B/B and B/D Plywood is a decorative NZ Radiata Pine that can be used in applications where strength and appearance are important. B/B and B/D plywood is ideal for finishing with stains, varnishes or oils and is very easy to cut and sand.

Density

450 – 500 kg/m³

Grade and Bond

B/B or B/D with Super E0 A Bond

Applications

- Furniture and Shelving
- Cabinets and Kickboards
- Wall Panelling and Displays
- Shop fitting



Thickness (mm)	Length x Width (mm)
18 (BB)	2400 x 1200
12 (BB)	2400 x 1200
12 (BD)	2400 x 1200



BB Lite Poplar Plywood

Trade Essentials® BB Lite Poplar is a lightweight, decorative Plywood, suitable for applications where finished weight is critical. Poplar is stable, flat and smooth with a light appearance. Poplar is ideally suited for CNC panels, as a substrate for laminating with HPL and for lightweight cabinetry.

Density

450 kg/m³

Grade and Bond

B/B with E0 Melamine Internal Glue

Applications

- Motorhome or boat cabinetry
- CNC Panelling
- Lightweight substrate for HPL
- Decorative Panelling



Thickness (mm)	Length x Width (mm)
18	2400 x 1200

Brownwood Plywood

Trade Essentials® Brownwood (Kuring) is a high density, high strength hardwood Plywood, with marine bonded glue lines. Brownwood is an ideal substitute for Meranti. The dark appearance of Brownwood gives additional aesthetic appeal and is suitable for use in cabinetry where a darker look is preferred. Brownwood Plywood gives a striking edge profile when exposed.

Density

700 – 850 kg/m³

Grade and Bond

B/C with E1 WBP

Applications

- Cabinetry
- Drawer fronts



Thickness (mm)	Length x Width (mm)
18	2440 x 1200
12	2440 x 1200

White HPL on Plywood

Trade Essentials® White HPL on Plywood is comprised of a Poplar core, laminated on both sides with either Gloss or Matt High Pressure Laminate (HPL) designed for use as a carcass material where extra durability is required. HPL has high wear resistance and is ideal for cabinetry applications in high use areas i.e. laundry, kitchens and bathrooms. Trade Essentials® HPL on Plywood is flat and smooth with a consistent thickness profile.

Density

450 – 500 kg/m³

Grade and Bond

HPL Laminate with E0 Melamine

Applications

- Kitchen cabinetry
- Wet area cabinetry
- Garage benches
- Industrial applications



Thickness (mm)	Length x Width (mm)
18 (Matt/Gloss)	2440 x 1220
16 (Matt/Gloss)	2440 x 1220





This versatile range of plywood is ideal for a host of applications including cabinetry, furniture, walls, ceilings and joinery. To capitalise on the deliberate design feature in residential and commercial settings of exposed timber, plywood is the perfect choice, leaving panels semi-exposed or utilising the laminated edge. Plywood also provides an effective solution for projects where panel weight is an important consideration.

VISIT US

laminex.co.nz

CALL US

0800 303 606

J009109 - 10/20 Internal use only

Trade Essentials® Plywood is marketed and distributed by Fletcher Building Products Limited trading as Laminex New Zealand™. © Copyright Reserved. 2020, Laminex New Zealand™. Trade Essentials® is the registered trademark of Fletcher Building Products Limited trading as Laminex New Zealand™. Laminex New Zealand™ is a trademark used under licence by Fletcher Building Products Limited trading as Laminex New Zealand™.

Laminex™
NEW ZEALAND